

### TECHNICAL SHEET

#### TYPICAL APPLICATIONS

- Medium weight carton sealing tape suitable for manual dispenser application. Also for automated application.



#### ADVANTAGES AND BENEFITS

- Excellent adhesion even in recycled cartons.
- Good tack.
- The adhesive high holding power value guarantees a long lasting adhesion and a safe storage even with temperature variations.

#### CONSTRUCTION

- Backing: Biaxially oriented polypropylene clear film.
- Adhesive: Synthetic rubber and hydrocarbon resins.
- Colour: Clear, white or brown adhesive.



#### TECHNICAL DATA

PP5120	METRIC
Film Thickness	28 Micron
Total Thickness	44 Micron
Peel Adhesion	5,2 N/cm
Tensile Strength	45 N/cm
Elongation at break	120%
Holding Power to Kraft @ 50°C in oven	9 hours
Application Temperature	6°C to 45°C
Service Temperature	-10°C to 60°C



Physical and performance characteristics shown above are obtained following tests recommended by AFERA and UBIS. The values given are typical values and do not constitute a specification. The user should determine whether the tape is suitable for the intended application.

#### STORAGE

Tape performance is guaranteed within the first 12 months. Product must be kept in its original box and in a dry atmosphere away from direct sunlight. For product traceability, please advise the 12 digit batch number printed on labels.

#### SECURITY

Product does not contain any dangerous or unhealthy components. Security data sheets are available based on directive 91/155/EC. All our tapes comply with European 2004/12/CE Packaging directive.