

Description:

Coated paper on the front side containing a layer of activated clay.

Colors available: White, yellow, blue, pink, green.

End uses:

Business forms, Invoices

Print methods:

Offset

Certificates:

- [FSC Chain of Custody \(multisite\)](#)
- [PEFC Chain of Custody \(multisite\)](#)
- [EMAS Leitzta mill](#)
- [OHSAS 18001 \(multisite\)](#)

Technical specifications

| Property | Test Method | Unit | Tolerance | 57 | 60 | 75 | 80 | 90 | 130 | 173 |
|-------------------|----------------------|------------------|-----------|------|------|------|------|------|------|------|
| Substance | ISO 536 | g/m ² | ±4% | 57 | 60 | 75 | 80 | 90 | 130 | 173 |
| Thickness | ISO 534 | µm | g≥130±10 | 63 | 66 | 81 | 99 | 109 | 157 | 207 |
| Opacity | ISO 2471 | % | ±4 | 80 | 81 | 85 | 88 | 92 | 95 | 97 |
| Relative humidity | TAPPI T502 OM -89 | % | ±5 | 43 | 43 | 43 | 40 | 40 | 40 | 40 |
| Curl | TAPPI T427 UM-85 | mm | (4.0)-0.0 | -2.0 | -2.0 | -2.0 | -2.0 | -2.0 | -2.0 | -2.0 |

GUARANTEES:

20 years legibility of the copy under normal conditions of storage (T: 15-25 °C and 50-60% RH).

5 years shelf life under normal conditions of storage and with the original packaging.

Values are subject to change without notice.

Last update: 12/05/2018