

Description:

Coated paper on both sides with microcapsules on the back and activated clay on the front. It is used as a middle sheet when more than two copies are needed. It can receive and transfer at the same time.

Colors available: White, yellow, blue, pink, green.

End uses:

Business forms, Invoices

Print methods:

Offset

Certificates:

- [FSC Chain of Custody \(multisite\)](#)
- [PEFC Chain of Custody \(multisite\)](#)
- [EMAS Leitza mill](#)
- [OHSAS 18001 \(multisite\)](#)

Technical specifications

Property	Test Method	Unit	Tolerance	45	53	60	75	90
Substance	ISO 536	g/m ²	±4%	45	53	60	75	90
Thickness	ISO 534	µm	±4	64	68	74	90	108
Opacity	ISO 2471	%	±4	77	79	81	88	91
Relative humidity	TAPPI T502 OM-89	%	±5	43	43	43	43	43
Curl	TAPPI T427 UM-85	mm	(4.0)-0.0	-2.0	-2.0	-2.0	-2.0	-2.0

GUARANTEES:

20 years legibility of the copy under normal conditions of storage (T: 15-25 °C and 50-60% RH).
 5 years shelf life under normal conditions of storage and with the original packaging.

Values are subject to change without notice.
 Last update: 12/05/2018